



# SRS6P21 RIVET SHAVER



**SRS6P21**

**Performance:**

Power: 0.6 hp (3.8 kw)  
Speed: 21,000 rpm

**Features:**

Pistol Grip

**Accessory:**

Stabilizer:  
74274A



**Rivet Shavers**



Model Number	Cutter Diameter		Free Speed rpm	Weight		Length		Side to Center		Maximum Air Consumption		Sound Level dB(A)
	in	mm		lb	kg	in	mm	in	mm	cfm	l/s	
<b>0.6 hp (3.8 kw) – Pistol Grip – 1/4"-28 Internal Thread</b>												
SRS6P21-5	5/16	8	21,000	2.0	0.9	6.5	165	0.8	21	25	12	84
SRS6P21-6	3/8	10	21,000	2.0	0.9	6.5	165	0.8	21	25	12	84
SRS6P21-7	7/16	11	21,000	2.0	0.9	6.5	165	0.8	21	25	12	84
SRS6P21-8	1/2	13	21,000	2.0	0.9	6.5	165	0.8	21	25	12	84
SRS6P21-9	9/16	14	21,000	2.0	0.9	6.5	165	0.8	21	25	12	84
SRS6P21-9W	9/16	14	21,000	2.0	0.9	6.5	165	0.8	21	25	12	84
SRS6P21-10	5/8	16	21,000	2.0	0.9	6.5	165	0.8	21	25	12	84

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure  
**Standard Equipment:** Parts List • Safety and Instruction Manual • Skirt • Comfort Grip (Pistol Grip models)

The locking microstop design allows an operator to hold the tool comfortably without concern for unintentionally changing the shaver depth. The depth of the cutter can be adjusted in .0005 inch increments.



**Rivet Shaver Skirts - 3/4-16 Thread**

Part Number	Cutter Diameter	
	in	mm
2925-5	5/16	8
2925-6	3/8	10
2925-7	7/16	11
2925-8B	1/2	13
2925-9	9/16	14
2925-9W	9/16	14
2925-10	5/8	16



**2925-8B**



**ATI429-B-6**

**Rivet Shaver Cutters - 1/4-28 Thread**

Part Number	Cutter Diameter	
	in	mm
ATI429B-1	5/16	8
ATI429B-2	3/8	10
ATI429B-3	7/16	11
ATI429B-4	1/2	13
ATI429B-5	9/16	14
ATI429B-6	5/8	16
ATI429B-7	3/4	19

**siouxtools.com**



250 Snap-on Drive  
P.O. Box 1596  
Murphy, North Carolina USA 28906  
PH: 828.835.9765  
FAX: 828.835.9685  
TOLL FREE: 866.259.7291  
TOLL FREE FAX: 800.722.7236

Benelux  
Tel: (N) +31-(0)880-104000  
(B) +32 (0)14-231967  
Fax: (N) +31-(0)880-104010  
(B) +32 (0)14-232627  
e-mail: (N) industrial.nl@snapon.com  
(B) industrial.be@snapon.com

Latin America  
Tel.: 305-271-0944  
Fax: 305-271-7152  
e-mail: latinamerica.caribbean@snapon.com

Germany  
Tel.: 49 2104 9509-0  
Fax: 49 2104 9509-99  
e-mail: indus.germany@snapon.com

Italy  
Tel.: 00 39 02 66 04 53 70  
Fax: 00 39 02 61 29 78 15  
e-mail: indus.italia@snapon.com

United Kingdom  
Tel.: 44 (0) 1536-413904  
Fax: 44 (0) 1536-413874  
e-mail: industrialuk@snapon.com

Asia  
Tel.: 65-6451-5570  
Fax: 65-6451-5574  
e-mail: esales.sg@snapon.com

Australia  
Tel.: 61 2 9837 9100  
Fax: 61 2 9624 2578  
e-mail:  
SOTA.customerservice@snapon.com



Distributed By:

