

Rapid Reverse Signature Series Drills

Features:

- Rapid Reverse
- Feathering Trigger
- Ergonomic Grip
- Light Weight Aluminum Housing
- Easy to Maintain 'Drop-in Motor'
- Low Noise
- 3 Planet Gear System
- 0.6 hp (0.45 kw)–1 hp (0.75 kw)
- Speed: 2000 rpm–2500 rpm
- Chuck Capacity: 3/8" (10 mm)



SDR6P20R3RR

Rapid Reverse Signature Series Screwdrivers

Features:

- Rapid Reverse
- Feathering Trigger (Teasing)
- Ergonomic Grip
- 1/4" Quick Change
- Light Weight Aluminum Housing
- Low Noise
- Easy to Maintain 'Drop-in Motor'
- Stall Drive or Positive Clutch
- 1 hp (0.75 kw)
- Speed: 2000 rpm



SSD10P20PRR

Rapid Reverse Signature Series Impact Driver

Features:

- Rapid Reverse
- High Power to Weight Ratio
- Extended Life Through Bearing Design
- Smooth Impacting that creates Minimal Torque Reaction
- 1/4" Quick Change
- 5000 BPM
- Speed: 4000 rpm



ID375AP-2QRR



DRILLS / ASSEMBLY | SIOUX TOOLS SIGNATURE SERIES PRODUCT BROCHURE

Rapid Reverse Pistol Grip Drills



Model Number	Chuck Capacity		Free Speed rpm	Weight		Length		Side To Center		Max. Air Consumption		Sound Level dB(A)	Spindle Thread
	in	mm		lb	kg	in	mm	in	mm	cfm	l/s		
.60 hp (0.45 kw) – Rapid Reverse													
SDR6P20R3RR	3/8	10	2000	2.3	1.00	6.3	160	0.8	20	25	12	80	3/8"-24
SDR6P25R3RR	3/8	10	2500	2.3	1.00	6.3	160	0.8	20	25	12	80	3/8"-24
SDR6P20RK3RR	3/8	10	2000	2.4	1.25	7.9	200	0.8	20	25	12	80	3/8"-24
1 hp (0.75 kw) – Rapid Reverse													
SDR10P20R3RR	3/8	10	2000	2.6	1.15	7.6	195	0.8	20	30	14	80	3/8"-24
SDR10P25R3RR	3/8	10	2500	2.6	1.15	7.6	195	0.8	20	30	14	80	3/8"-24

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
Standard Equipment: Parts List • Safety and Instruction Manual • 3-jaw Chuck and Key • Comfort Grip



SDR6P20R3RR



SDR10P20R3RR

Rapid Reverse Pistol Grip Screwdrivers



Model Number	Max Torque ¹ (Soft Joint)		Free Speed rpm	Weight		Length		Side To Center		Air Consumption		Sound Level dB(A)
	in lb	Nm		lb	kg	in	mm	in	mm	cfm	l/s	
1 HP (0.75 kw) – Medium Torque Positive Clutch Rapid Reverse Screwdriver												
SSD10P20PRR	70	7.9	2000	2.4	1.07	7.3	185	0.8	20	30	14	80
1 hp (0.75 kw) – Stall Rapid Reverse												
SSD10P20SRR	80	9.0	2000	2.2	0.98	6.5	165	0.8	20	30	14	80

¹ Torque output varies with force exerted by operator

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
Standard Equipment: Parts List • Safety and Instruction Manual • Comfort Grip



SSD10P20SRR



SSD10P20PRR

1/4" (6 mm) Rapid Reverse Impact Driver



Model Number	Drive Size		Working Torque Range ¹		Maximum Torque		Blows Per Minute	Free Speed rpm	Weight		Length		Side To Center		Socket Retainer Style
	in	mm	ft lb	Nm	ft lb	Nm			lb	kg	in	mm	in	mm	
ID375AP-2QRR	1/4	6	10-55	13-75	60	80	5000	4000	2.5	1.1	8.5	216	085	21	Quick Change

Pistol Grip Impact Driver



ID375AP-2QRR

¹ Maximum working torque determined by 5 second rundown on appropriate Skidmore-Wilhelm Torque-Tension Tester.

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
Standard Equipment: Parts List • Safety and Instruction Manual

siouxtools.com



250 Snap-on Drive
 P.O. Box 1596
 Murphy, North Carolina USA 28906
 PH: 828.835.9765
 FAX: 828.835.9685
 TOLL FREE: 866.259.7291
 TOLL FREE FAX: 800.722.7236

Benelux
 Tel: (N) +31-(0)880-104000
 (B) +32 (0)14-231967
 Fax: (N) +31-(0)880-104010
 (B) +32 (0)14-232627
 e-mail: (N) industrial.nl@snapon.com
 (B) industrial.be@snapon.com

Latin America
 Tel.: 305-271-0944
 Fax: 305-271-7152
 e-mail: latinamerica.caribbean@snapon.com

Germany
 Tel.: 49 2104 9509-0
 Fax: 49 2104 9509-99
 e-mail: indus.germany@snapon.com

Italy
 Tel.: 00 39 02 66 04 53 70
 Fax: 00 39 02 61 29 78 15
 e-mail: indus.italia@snapon.com

United Kingdom
 Tel.: 44 (0) 1536-413904
 Fax: 44 (0) 1536-413874
 e-mail: industrialuk@snapon.com

Asia
 Tel.: 65-6451-5570
 Fax: 65-6451-5574
 e-mail: esales.sg@snapon.com

Australia
 Tel.: 61 2 9837 9100
 Fax: 61 2 9624 2578
 e-mail:
 SOTA.customerservice@snapon.com



Distributed By:

