

## Rapid Reverse Signature Series Drills

### Features:

- Rapid Reverse
- Feathering Trigger
- Ergonomic Grip
- Light Weight Aluminum Housing
- Easy to Maintain 'Drop-in Motor'
- Low Noise
- 3 Planet Gear System
- 0.6 hp (0.45 kw)–1 hp (0.75 kw)
- Speed: 2000 rpm–2500 rpm
- Chuck Capacity: 3/8" (10 mm)



**SDR6P20R3RR**

## Rapid Reverse Signature Series Screwdrivers

### Features:

- Rapid Reverse
- Feathering Trigger (Teasing)
- Ergonomic Grip
- 1/4" Quick Change
- Light Weight Aluminum Housing
- Low Noise
- Easy to Maintain 'Drop-in Motor'
- Stall Drive or Positive Clutch
- 1 hp (0.75 kw)
- Speed: 2000 rpm



**SSD10P20PRR**

## Rapid Reverse Signature Series Impact Driver

### Features:

- Rapid Reverse
- High Power to Weight Ratio
- Extended Life Through Bearing Design
- Smooth Impacting that creates Minimal Torque Reaction
- 1/4" Quick Change
- 5000 BPM
- Speed: 4000 rpm



**ID375AP-2QRR**



# DRILLS / ASSEMBLY | SIOUX TOOLS SIGNATURE SERIES PRODUCT BROCHURE

## Rapid Reverse Pistol Grip Drills



Model Number	Chuck Capacity		Free Speed rpm	Weight		Length		Side To Center		Max. Air Consumption		Sound Level dB(A)	Spindle Thread
	in	mm		lb	kg	in	mm	in	mm	cfm	l/s		
<b>.60 hp (0.45 kw) – Rapid Reverse</b>													
SDR6P20R3RR	3/8	10	2000	2.3	1.00	6.3	160	0.8	20	25	12	80	3/8"-24
SDR6P25R3RR	3/8	10	2500	2.3	1.00	6.3	160	0.8	20	25	12	80	3/8"-24
SDR6P20RK3RR	3/8	10	2000	2.4	1.25	7.9	200	0.8	20	25	12	80	3/8"-24
<b>1 hp (0.75 kw) – Rapid Reverse</b>													
SDR10P20R3RR	3/8	10	2000	2.6	1.15	7.6	195	0.8	20	30	14	80	3/8"-24
SDR10P25R3RR	3/8	10	2500	2.6	1.15	7.6	195	0.8	20	30	14	80	3/8"-24

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure  
**Standard Equipment:** Parts List • Safety and Instruction Manual • 3-jaw Chuck and Key • Comfort Grip



SDR6P20R3RR



SDR10P20R3RR

## Rapid Reverse Pistol Grip Screwdrivers



Model Number	Max Torque <sup>1</sup> (Soft Joint)		Free Speed rpm	Weight		Length		Side To Center		Air Consumption		Sound Level dB(A)
	in lb	Nm		lb	kg	in	mm	in	mm	cfm	l/s	
<b>1 HP (0.75 kw) – Medium Torque Positive Clutch Rapid Reverse Screwdriver</b>												
SSD10P20PRR	70	7.9	2000	2.4	1.07	7.3	185	0.8	20	30	14	80
<b>1 hp (0.75 kw) – Stall Rapid Reverse</b>												
SSD10P20SRR	80	9.0	2000	2.2	0.98	6.5	165	0.8	20	30	14	80

<sup>1</sup> Torque output varies with force exerted by operator

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure  
**Standard Equipment:** Parts List • Safety and Instruction Manual • Comfort Grip



SSD10P20SRR



SSD10P20PRR

## 1/4" (6 mm) Rapid Reverse Impact Driver



Model Number	Drive Size		Working Torque Range <sup>1</sup>		Maximum Torque		Blows Per Minute	Free Speed rpm	Weight		Length		Side To Center		Socket Retainer Style
	in	mm	ft lb	Nm	ft lb	Nm			lb	kg	in	mm	in	mm	
ID375AP-2QRR	1/4	6	10-55	13-75	60	80	5000	4000	2.5	1.1	8.5	216	085	21	Quick Change

### Pistol Grip Impact Driver



ID375AP-2QRR

<sup>1</sup> Maximum working torque determined by 5 second rundown on appropriate Skidmore-Wilhelm Torque-Tension Tester.

**General:** Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure  
**Standard Equipment:** Parts List • Safety and Instruction Manual

siouxtools.com



250 Snap-on Drive  
 P.O. Box 1596  
 Murphy, North Carolina USA 28906  
 PH: 828.835.9765  
 FAX: 828.835.9685  
 TOLL FREE: 866.259.7291  
 TOLL FREE FAX: 800.722.7236

Benelux  
 Tel: (N) +31-(0)880-104000  
 (B) +32 (0)14-231967  
 Fax: (N) +31-(0)880-104010  
 (B) +32 (0)14-232627  
 e-mail: (N) industrial.nl@snapon.com  
 (B) industrial.be@snapon.com

Latin America  
 Tel.: 305-271-0944  
 Fax: 305-271-7152  
 e-mail: latinamerica.caribbean@snapon.com

Germany  
 Tel.: 49 2104 9509-0  
 Fax: 49 2104 9509-99  
 e-mail: indus.germany@snapon.com

Italy  
 Tel.: 00 39 02 66 04 53 70  
 Fax: 00 39 02 61 29 78 15  
 e-mail: indus.italia@snapon.com

United Kingdom  
 Tel.: 44 (0) 1536-413904  
 Fax: 44 (0) 1536-413874  
 e-mail: industrialuk@snapon.com

Asia  
 Tel.: 65-6451-5570  
 Fax: 65-6451-5574  
 e-mail: esales.sg@snapon.com

Australia  
 Tel.: 61 2 9837 9100  
 Fax: 61 2 9624 2578  
 e-mail:  
 SOTA.customerservice@snapon.com



Distributed By:

