



RECIPROCATING SAW



RS10K

Features:

- Lock-off lever start
- Low vibration
- 360° Adjustable Exhaust Deflector
- Dual chuck accepts 0.035" standard air saw blades AND 6" long reciprocating saw blades
- Cuts up to 1/8" (3 mm) mild steel

Reciprocating Saw

Model Number	Free Speed	Stroke Length		Strokes per Minute	Weight		Length		Air Consumption		Sound Level
	rpm	in	mm		lb	kg	in	mm	cfm	l/s	dB(A)
RS10K	10,000	0.375	10	10,000	1.53	0.69	9.4	238.76	1.0	0.5	87.1

General:

Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment:

Parts List • Safety and Instruction Manual • Swivel Air Inlet • 2 Blades • Protective Boot

siouxtools.com



250 Snap-on Drive
 P.O. Box 1596
 Murphy, North Carolina USA 28906
 PH: 828.835.9765
 FAX: 828.835.9685
 TOLL FREE: 866.259.7291
 TOLL FREE FAX: 800.722.7236

Benelux
 Tel: (N) +31-(0)880-104000
 (B) +32 (0)14-231967
 Fax: (N) +31-(0)880-104010
 (B) +32 (0)14-232627
 e-mail: (N) industrial.nl@snapon.com
 (B) industrial.be@snapon.com

Latin America
 Tel.: 305-271-0944
 Fax: 305-271-7152
 e-mail: latinamerica.caribbean@snapon.com

Germany
 Tel.: 49 2104 9509-0
 Fax: 49 2104 9509-99
 e-mail: indus.germany@snapon.com

Italy
 Tel.: 00 39 02 66 04 53 70
 Fax: 00 39 02 61 29 78 15
 e-mail: indus.italia@snapon.com

United Kingdom
 Tel.: 44 (0) 1536-413904
 Fax: 44 (0) 1536-413874
 e-mail: industrialuk@snapon.com

Asia
 Tel.: 65-6451-5570
 Fax: 65-6451-5574
 e-mail: esales.sg@snapon.com

Australia
 Tel: 61 2 9837 9100
 Fax: 61 2 9624 2578
 e-mail:
 SOTA.customerservice@snapon.com



Distributed By:

