



FINISHING

Making It Easy To Finish The Work

If you're in the market for tough tools that will deliver the performance you demand, then you've found what you need with Force sanders, polishers and buffers. These exceptional tools take on any application from repair and maintenance to manufacturing. With state-of-the-art orbital sanders, polishers and buffers you will get your work done faster and more efficiently than ever.



SANDERS & POLISHERS



5540

Features:

- Aluminum Housing
- Built-in Speed Regulator

Pistol Grip Sander



Model Number	Free Speed	Weight		Length		Avg Air Consumption		Spindle Thread
	rpm	lb	kg	in	mm	cfm	l/s	
5540	14000	2.2	1.0	4.3	109	12	6	7/16"-20

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm)

Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: 3" (75 mm) and 4-1/2" (115 mm) backing pads included • Parts List Safety and Instruction Manual

Features:

- Lockoff lever throttle
- Safety lever throttle
- Removable auxiliary handle and wrenches
- Built-in speed regulator
- Rear exhaust



5265

5" (125 mm) Right Angle Air Sander



Model Number	Free Speed	Weight		Length		Avg Air Consumption		Spindle Thread
	rpm	lb	kg	in	mm	cfm	l/s	
5265	7000	2.9	1.32	9.4	1.32	4.5	2	5/8"-11

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Backing pad for 5" (125 mm) abrasives included • Parts List • Safety and Instruction Manual



SANDERS & POLISHERS

Features:

- Lockoff lever throttle
- Support handle can be mounted on either side
- Rear exhaust

Right Angle Sander



Model Number	Free Speed	Weight		Length		Avg Air Consumption		Spindle Thread
	rpm	lb	kg	in	mm	cfm	l/s	
5287A	6000	4.4	2.0	12.6	320	4.8	2.3	5/8"-11

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm)
Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Backing pad for 7" (180 mm) abrasives included • Parts List
Safety and Instruction Manual



5287A

Features:

- Dual handles
- Positive lock paper clamps
- Paper size: 2-3/4" x 17-1/2" (70 x 445 mm)

Dual Piston Inline Sander

Model Number	Strokes Per Minute	Weight		Length		Avg Air Consumption	
		lb	kg	in	mm	cfm	l/s
5560	2500	6.8	3.1	16.0	406	3	1

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Backing pad for 7" (180 mm) abrasives included • Parts List • Safety and Instruction Manual



5560

Features:

- Built-in speed regulator
- Dual action sanding
- Vinyl grip and head cover

Dual Action Sander

Model Number	Orbit Diameter		Free Speed	Weight		Height		Avg Air Consumption	
	in	mm	rpm	lb	kg	in	mm	cfm	l/s
5558A	3/8	10	10000	4.3	2.0	5.4	137	5	2

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: 6" (150 mm) backing pad included • Parts List • Safety and Instruction Manual



5558A



FINISHING ACCESSORIES



Orbital Sander Backing Pads

Sioux random orbital backing pads are medium density, urethane pads rated for speeds up to 13,000 rpm. The 5" pads are a 3/8" thick with low profile design, while the 6" pads are 5/8" thick with tapered profile for fine feathering in corners or around edges.

Part Number	Diameter		Backing	Profile	Style
	in	mm			
593	5	125	PSA ¹	Low	Non-Vac
593V	5	125	PSA ¹	Low	Vacuum
593J	5	125	H&L ²	Low	Non-Vac
593JV	5	125	H&L ²	Low	Vacuum
593SV	5	125	PSA ¹	Low	Screen Vac
594	6	150	PSA ¹	Tapered	Non-Vac
594V	6	150	PSA ¹	Tapered	Vacuum
594J	6	150	H&L ²	Tapered	Non-Vac
594JV	6	150	H&L ²	Tapered	Vacuum
594SV	5	125	PSA ¹	Low	Screen Vac

¹ PSA - Vinyl face for pressure sensitive adhesive sanding discs

² H&L - Hook and loop face



Part Number	Thread	Diameter	
		in	mm
2344	(3/8-24) & (5/8-11)	5	125

Includes disc nut 563



Part Number	Diameter		For Use On
	in	mm	
5205+	5	125	5265
5207*	7	180	5287A

*includes disc nut No. 67630

+does not include disc nut No. 67630 (order separately)



587M



588M

Speed-Lok Backing Pads

For use on tools with 1/4" collets

Part Number	Diameter		Hex Size
	in	mm	
587M	2	50	1/4"
588M	3	75	1/4"

Fibre Backing Discs

Part No. 586

For use on 5540 series sander

Packaged in cartons of 6

Qty 3 - 3" (75 mm)

Qty 3 - 4-1/2" (110 mm)

Both have 7/8" (22 mm) arbor hole



SP505079

Part Number	Diameter		For Use On
	in	mm	
SP505079	2.75 X 17.5	70 X 445	5560