



TORQUE CONTROL SCREWDRIVERS

Shut Off Clutch Screwdrivers



SSD4P22TCRR

Features:

- Push to Start
- Shuts Off When Reaches Torque
- #1 Phillips Clutch Adjustment
- Rapid-Reverse – Momentary or Twist-Lock Reverse
- 0.4 hp in Compact Size
- Ergonomic Grip and Finger Rest
- Ease of Service



Model Number	Torque Range		Free Speed	Weight		Length		Side To Center		Air Consumption Free Speed	
	in lb	Nm	rpm	lb	kg	in	mm	in	mm	scfm	l/s
0.4 hp (0.3 kW) Push to Start - Rapid Reverse											
SSD4P5TCRR	5-50	0.6-5.5	500	2.2	1.0	8.7	220	0.7	20	20	9
SSD4P11TCRR	5-40	0.6-4.5	1100	2.2	1.0	8.7	220	0.7	20	20	9
SSD4P22TCRR	5-20	0.6-2.3	2200	1.9	0.9	8.2	210	0.7	20	20	9

Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

siouxtools.com



250 Snap-on Drive
P.O. Box 1596
Murphy, North Carolina USA 28906
PH: 828.835.9765
FAX: 828.835.9685
TOLL FREE: 866.259.7291
TOLL FREE FAX: 800.722.7236

Belgium
Tel.: 32 (0)14 23 19 67
Fax: 32 (0)14 23 26 27
Email: Industrial.be@snapon.com

Netherlands
Tel.: 31 (0)88 0104000
Fax: 31 (0)88 0104010
Email: Industrial.nl@snapon.com

Latin America
Tel.: 786-254-7765
Fax: 786-534-9350
e-mail: latinamerica.caribbean@snapon.com

Germany
Tel.: 49 2104 9509-0
Fax: 49 2104 9509-99
e-mail: indus.germany@snapon.com

Italy
Tel.: 00 39 02 66 04 53 70
Fax: 00 39 02 61 29 78 15
e-mail: indus.italia@snapon.com

United Kingdom
Tel.: 44 (0) 1536-413904
Fax: 44 (0) 1536-413874
e-mail: industrialuk@snapon.com

Asia
Tel.: 65-6451-5570
Fax: 65-6451-5574
e-mail: esales.sg@snapon.com

Australia
Tel.: 61 2 9837 9100
Fax: 61 2 9624 2578
e-mail:
SOTA.customerservice@snapon.com