

FINISHING



Making It Easy To Finish The Work

If you're in the market for tough tools that will deliver the performance you demand, then you've found what you need with Force sanders. These exceptional tools take on any application from repair and maintenance to manufacturing. Get your work done faster and more efficiently than ever.



SANDERS & POLISHERS



5540C

Features:

- Aluminum Housing
- Built-in Speed Regulator
- Comfort Grip

Pistol Grip Sander



Model Number	Free Speed	Weight		Length		Air Consumption		Spindle Thread
	rpm	lb	kg	in	mm	scfm	l/s	
0.6 hp (0.45 kW)								
5540C	13000	2.2	1.0	4.3	109	28	13	7/16"-20

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
Standard Equipment: 3" (75 mm) and 4-1/2" (115 mm) backing pads • Parts List • Safety and Instruction Manual • Spindle Wrenches



5265C

Features:

- Lockoff lever throttle
- Built-in speed regulator
- Rear exhaust

5" (125 mm) Right Angle Air Sander



Model Number	Free Speed	Weight		Length		Air Consumption		Spindle Thread
	rpm	lb	kg	in	mm	scfm	l/s	
0.7 hp (0.5 kW)								
5265C	7000	2.9	1.32	9.4	1.32	33	16	5/8"-11

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure
Standard Equipment: Backing pad for 5" (125 mm) abrasives • Parts List • Safety and Instruction Manual • Spindle Wrenches



SANDERS

Features:

- Lockoff lever throttle
- Support handle can be mounted on either side
- Rear exhaust

7" (175 mm) Right Angle Sander



Model Number	Free Speed	Weight		Length		Air Consumption		Spindle Thread
	rpm	lb	kg	in	mm	scfm	l/s	
0.7 hp (0.5 kW)								
5287C	6000	4.4	2.0	12.6	320	35	17	5/8"-11



5287C

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm)

Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Backing pad for 7" (175 mm) abrasives • Parts List
Safety and Instruction Manual • Spindle Wrenches

Features:

- Built-in speed regulator
- Dual action sanding
- Vinyl grip and head cover

Dual Action Sander



5558C

Model Number	Orbit Diameter		Free Speed	Weight		Height		Air Consumption	
	in	mm	rpm	lb	kg	in	mm	scfm	l/s
0.7 hp (0.5 kW)									
5558C	3/8	10	10000	4.3	2.0	5.4	137	28	13

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: 6" (150 mm) backing pad • Parts List • Safety and Instruction Manual

Features:

- Dual handles
- Positive lock paper clamps
- Paper size: 2-3/4" x 17-1/2" (70 x 445 mm)

Dual Piston Inline Sander



5560

Model Number	Strokes Per Minute	Weight		Length		Air Consumption	
		lb	kg	in	mm	scfm	l/s
5560	2500	6.8	3.1	16.0	406	21	10

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Backing pad • Parts List • Safety and Instruction Manual